



**Artifacts™**  
66-1/8" x 32-1/2" freestanding bath  
**K-21000-PAT**

## Features

- Freestanding design creates a striking focal point in your bathing area
- Integral lumbar support on both ends
- Safeguard® slip-resistant surface provides excellent traction underfoot
- Painted exterior in Teal
- Coordinates with other products in the Artifacts collection

## Material

- KOHLER® enameled cast iron



## Installation

- Freestanding
- Requires K-7159 drain (sold separately)
- Requires K-204 ball-and-claw feet (sold separately)

## Required Products/Accessories

- K-204 Ball-and-claw feet
- K-7159 1-1/2" pop-up bath drain for freestanding baths

## Recommended Products/Accessories

- K-23725 Cast iron cleaner
- K-23726 Drain treatment

## Codes/Standards

ASME A112.19.1/CSA B45.2  
ASTM F462

## KOHLER® Enamelled Cast Iron Bath and Shower Base Lifetime Limited Warranty

See website for detailed warranty information.

## Available Colors/Finishes




*Color tiles intended for reference only.*

### Color Code Description

|  |    |             |
|--|----|-------------|
|  | 0  | White       |
|  | 17 | Teal        |
|  | 34 | Fresh Green |
|  | 42 | Aspen Green |



**Artifacts™**  
66-1/8" x 32-1/2" freestanding bath  
**K-21000-PAT**



## Technical Information

All product dimensions are nominal.

|                     |   |
|---------------------|---|
| Drain location:     | Center  |
| Basin area, bottom: | 48-15/16" x 24-3/4" (1243 mm x 629 mm)            |
| Basin area, top:    | 58-11/16" x 27-13/16" (1491 mm x 706 mm)          |
| Weight:             | 396.2 lbs (179.7 kg)                              |
| Minimum floor load: | 90 lbs/ft <sup>2</sup> (439.4 kg/m <sup>2</sup> ) |
| Water depth:        | 14-3/8" (366 mm)                                  |
| Water capacity:     | 69 gal (261.2 L)                                  |
| Template:           | 1344921-7, not required, not included             |

## Notes

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.